



Lubrication pump

* no illustrated

Item	Description	NO.
1*	Lubrication Pump complete ratio of reduction 2,3:1	13.10.30
2*	Oil Pump Drive complete with horizontal drive shaft and worm gear	13.10.31
3	horizontal drive shaft	13.10.29
4	worm gear	13.10.08
5	spacing shim for horizontal drive shaft 0,1mm	13.10.10
	spacing shim for horizontal drive shaft 0,2mm	13.10.11
	spacing shim for horizontal drive shaft 0,3mm	13.10.12
6	slotted taper pin	13.10.13
7	flange bearing	13.10.14
8	setscrew	13.10.15
9	drive disk	13.10.70
10	drive lock disk	13.10.71
11	snapping	13.10.18
12	roller	13.10.72
13	shoulder pin	13.10.20
14	spring	13.10.21
15	woodruff key	13.10.22
16	ring disk	13.10.23
17	snap ring	13.10.24
18	rocking lever	13.10.25
19	bearing sleeve	13.10.26
20	hexagon nut M 10 x 1	13.10.27
21	lock washer A 10	14.26.04
22	screw plug R 1/8"	13.10.67
23	vertical drive shaft	13.10.40
24	worm gear	13.10.42
25	working swash plate	13.10.43
26	swash plate bearing sleeve	13.10.44
27	woodruff key	13.10.45
28	control swash plate	13.10.46
29	spacer tube	13.10.47
30	spacing shim for drive shaft 0,1mm	13.10.48
	spacing shim for drive shaft 0,2mm	13.10.49
	spacing shim for drive shaft 0,3mm	13.10.50
31	washer	13.10.51



Lubrication pump

* no illustrated

Item	Description	NO.
32	crown nut	13.10.52
33	split pin 2 x 22	2.16.07
34	pump element	13.10.09
35	fastening screw	13.10.53
36	suction sieve	13.10.54
37	cylindrical screw 4 x 6	13.10.55
38	wick casing	13.10.56
39	lubrication wick	13.10.57
40	hexagon nut M 8	1.10.18
41	hexagon nut	13.10.58
42	filling strainer	13.10.59
43	filling cover	13.10.60
44	gasket	13.10.03
45	countersunk screw M 6 x 50	13.10.06
46	rocking lever extension	13.10.61
47	hexagon screw M 8 x 25	13.10.62
(40)	hexagon nut M 8	1.10.18
48	lock washerA 8	14.75.53
49	hand crank short type	13.10.65
50	hand crank long type	13.10.66

